PADDY LEAF DISEASE CLASSIFICATION USING EFFICIENT NET B4 WITH COMPOUND SCALING AND SWISH ACTIVATION :A DEEP LEARNING APPROACH

Shaik Sharmila[1], Shaik Sana Nawaz[2], Shaik Ismath Unnisa[3], Ms. Fatima Aladdin[4]
[1,2,3]UG Scholar, Dept of CSE, Shadan Women's College of Engineering and Technology, Hyderabad,
[4]Asst. Professor, Dept of CSE, Shadan Women's College of Engineering and Technology

ABSTRACT

Paddy leaf diseases are a significant concern for rice farmers globally, as they can lead to severe reductions in crop yield and quality, threatening food security and economic stability in rice-dependent regions. Traditional methods of disease detection rely on manual inspection by experts, which is not only time-consuming and costly but also infeasible for large-scale farms. Moreover, such methods are prone to human error and inconsistencies, particularly in early stages when visual symptoms may be subtle. Addressing this critical issue, our study proposes an automated, high-accuracy classification approach for paddy leaf disease detection using an Xception-based deep learning model. The Xception model, known for its depthwise separable convolution architecture, is fine-tuned and adapted to capture the nuanced patterns of various paddy diseases, such as bacterial blight, brown spot, and leaf smut. Initialized with ImageNet weights, the model is further refined with custom layers to enhance its specificity and robustness in recognizing complex disease features specific to paddy leaves. This customization ensures that the model is highly sensitive to slight variations in leaf texture, color, and shape caused by different pathogens, allowing it to classify multiple disease types effectively. To optimize model performance, we employ the Adam optimizer and categorical cross-entropy loss function, which helps achieve smooth and reliable convergence. The proposed model not only serves as a tool for accurate disease classification but also supports early detection, which is crucial for timely intervention and preventing disease spread. By enabling real-time disease monitoring, this approach aids farmers in applying precise treatment, minimizing the excessive use of pesticides, and reducing environmental impact. Furthermore, this method can be integrated into mobile or IoT-based solutions, making it accessible for rural and resource-limited settings. Ultimately, our work contributes to sustainable agriculture by empowering farmers with a scalable, low-cost solution for disease management, safeguarding crop yields, and promoting food security.

INTRODUCTION

Rice is a fundamental crop that sustains over half of the world's population, serving as a dietary staple and a major economic resource in many developing countries. Ensuring high-quality rice production is therefore essential not only for food security but also for the economic stability of rice-dependent regions. However, paddy leaf diseases present a constant threat to rice cultivation, leading to substantial declines in crop yield, quality, and profitability. These diseases, including bacterial blight, brown spot, leaf smut, and rice blast, are caused by various bacterial, fungal, and viral pathogens that can spread quickly under favorable environmental conditions. Once diseases establish, they are challenging to control, especially in large paddy fields, where timely detection and accurate identification are crucial for minimizing their impact. Left unmanaged, these diseases can cause economic devastation for farmers, increase food insecurity, and lead to ecological harm through increased pesticide use.

The traditional approach to paddy leaf disease diagnosis relies on manual visual inspection by experts who look for specific symptoms, such as lesions, discoloration, blight, or spotting patterns on the leaves. This approach, while effective to some extent, has several limitations. Manual inspection is labor-intensive, subjective, and often infeasible for large fields, especially when expertise is limited or costly. In rural or remote regions, where the majority of rice farming takes place, access to trained personnel may be sparse, further delaying diagnosis and intervention. Additionally, manual methods are prone to inconsistencies due to human error and can miss early signs of disease, which are critical for timely intervention. These challenges underscore the need for an automated, scalable solution that can provide rapid, reliable, and accurate disease classification without dependence on specialist availability. With advancements in technology, digital agriculture has emerged as a solution to many of these issues, leveraging tools such as IoT, mobile applications, and machine learning. Deep learning, particularly in image processing, has proven effective for visual tasks, offering a powerful solution for automated disease identification. The use of image-based disease classification can provide several benefits: it enables early detection, reduces reliance on expert labor, and can be deployed in real-time through mobile devices or field sensors. Early and accurate disease identification allows for timely interventions, such as the application of targeted pesticides, selective pruning, or the use of resistant crop varieties, which helps contain outbreaks while reducing the environmental impact of farming practices.

This project aims to develop a high-performance, automated system for paddy leaf disease classification, which can empower farmers and agricultural workers with accessible tools for disease management. By building a robust classification model, this project seeks to create an adaptable solution that can be integrated into mobile

applications or IoT frameworks, enabling farmers to monitor crop health directly in the field with minimal technical training. Additionally, the project is intended to address several broader goals: promoting food security by safeguarding rice yields, supporting the economic stability of rice-growing communities, and advancing sustainable agricultural practices by minimizing the need for indiscriminate pesticide application. In summary, an automated paddy leaf disease classification system would enable precision agriculture practices, equipping farmers with valuable insights for proactive disease management. This solution has the potential to transform disease management in rice farming by making it more accurate, accessible, and sustainable, thus playing a vital role in securing global food supplies and supporting agricultural resilience in the face of growing environmental challenges.

SCOPE OF THE PROJECT

The scope of this project is centered around developing an automated, high-performance system for the classification of paddy leaf diseases using deep learning techniques. The primary goal is to create a model capable of accurately identifying and classifying common paddy leaf diseases, such as bacterial blight, brown spot, and leaf smut, based on images of the leaves. By leveraging deep learning, specifically the Xception architecture, the system aims to provide reliable and fast disease detection that can be used in real-time by farmers and agricultural workers. This project will involve collecting a comprehensive dataset of paddy leaf images, preprocessing these images for use in training the model, and developing a robust deep learning model capable of classifying multiple disease types with high accuracy. In addition to disease classification, the scope extends to integrating the system into practical agricultural tools, such as mobile applications or IoT-based platforms, allowing farmers to use the model for real-time monitoring of their crops. The system will be designed to function in resource-limited rural environments, offering a user-friendly interface and low-cost deployment options. Furthermore, the project aims to contribute to sustainable agricultural practices by reducing the overuse of pesticides and enabling more targeted disease management. Ultimately, the scope includes not only the technical development of the disease classification model but also the exploration of its real-world applications in supporting food security, improving agricultural efficiency, and promoting eco-friendly farming practices.

OBJECTIVE

The objective of this project is to develop an advanced deep learning-based system that automatically classifies paddy leaf diseases to support early detection and efficient disease management in rice farming. The primary goal is to design and implement a deep learning model, based on the Xception architecture, capable of accurately identifying and classifying common paddy leaf diseases such as bacterial blight, brown spot, and leaf smut, using high-quality leaf images. The model will be trained on a comprehensive dataset of labeled leaf images, ensuring that it can differentiate between various disease types. Additionally, the project aims to optimize the model for high accuracy and generalization, with fine-tuning of the Xception architecture to specifically handle paddy leaf disease features. A secondary objective is to develop a user-friendly platform or mobile application that allows farmers to easily upload images of their crops for instant disease diagnosis. By enabling rapid disease detection, this system will help farmers make informed decisions for timely interventions. Ultimately, the project aims to contribute to sustainable agricultural practices by promoting early disease identification, reducing the overuse of pesticides, and enhancing crop management, thereby supporting food security and environmental sustainability.

EXISTING SYSTEM:

The existing model, represents a significant advancement in the application of deep learning to agricultural disease detection, particularly in the context of paddy leaf diseases. This model utilizes the EfficientNet B4 architecture, a highly efficient convolutional neural network that employs compound scaling to optimize model performance across all dimensions (depth, width, and resolution). EfficientNet B4 is known for its ability to achieve state-of-the-art performance while maintaining relatively low computational complexity, making it an ideal choice for large-scale image classification tasks, such as the identification of paddy leaf diseases.

Compound scaling, a key feature of EfficientNet, allows the model to scale efficiently across different levels, striking a balance between accuracy and computational cost. This approach enables the model to learn from a broader range of features, improving its ability to recognize and classify subtle variations in leaf images caused by different diseases. Additionally, the use of Swish activation function known for their ability to enhance model training and performance by avoiding issues like the vanishing gradient problem further contributes to the model's robustness and efficiency. The model has been specifically designed to handle the classification of multiple paddy leaf diseases, including bacterial blight, brown spot, leaf smut, and other common rice diseases. With its ability to process high-resolution leaf images, the existing model delivers reliable results and high classification performance. However, despite its effectiveness, challenges remain, such as the need for large, high-quality

labeled datasets, and the system's computational demands, which can hinder its deployment in real-time or on resource-constrained devices.

Overall, while the existing model provides strong performance and efficiency, its complexity and resource requirements make it more suited for environments with access to sufficient computational power. This model has laid the groundwork for further advancements in automated paddy leaf disease classification, but there is still room for improvement in terms of accessibility, real-time implementation, and scalability, especially for low-resource farmers.

Existing System Disadvantages:

- Computationally Intensive: EfficientNet B4 requires significant computational resources, making it challenging for real-time deployment in resource-constrained environments.
- Large Labeled Datasets Required: The model's performance heavily depends on large, high-quality annotated datasets, which may be difficult to obtain.
- Limited Real-Time Application: Due to its complexity, the model may struggle with real-time processing, particularly in field environments with limited infrastructure.
- Generalization Issues: The model may face difficulties generalizing to new geographical regions or unfamiliar disease symptoms caused by varying environmental conditions.

LITERATURE SURVEY

An optimized capsule neural networks for tomato leaf disease classification**,** L. M. Abouelmagd, M. Y. Shams, H. S. Marie, and A. E. Hassanien, 2024.

The paper titled "An Optimized Capsule Neural Networks for Tomato Leaf Disease Classification" by L. M. Abouelmagd, M. Y. Shams, H. S. Marie, and A. E. Hassanien, published in EURASIP Journal on Image and Video Processing in January 2024, presents a novel approach to classifying tomato leaf diseases using Capsule Neural Networks (CapsNet). Capsule Networks are a type of deep learning architecture designed to capture spatial hierarchies and relationships between parts of an object, which makes them more robust to variations in input data, such as rotation and orientation. The paper focuses on optimizing CapsNet for improved performance in the classification of tomato leaf diseases. Traditional deep learning models struggle with recognizing objects under different orientations, and this is where CapsNet shows promise, as it can preserve and recognize relationships between features in an image. The authors explore various optimization techniques, likely involving hyperparameter tuning, advanced training strategies, or innovative network configurations, to enhance the model's ability to correctly identify disease symptoms from tomato leaves. In their study, they likely compare the performance of the optimized Capsule Network against other traditional deep learning models, demonstrating its superiority or complementarity in terms of accuracy, robustness, and efficiency. This research contributes to agricultural automation by providing a more reliable and effective tool for disease detection in crops, particularly tomatoes, which can help farmers take timely actions to control outbreaks and improve crop yields.

Enhancing crop recommendation systems with explainable artificial intelligence: A study on agricultural decision-making, M. Y. Shams, S. A. Gamel, and F. M. Talaat, 2024.

The paper titled "Enhancing Crop Recommendation Systems with Explainable Artificial Intelligence: A Study on Agricultural Decision-Making" by M. Y. Shams, S. A. Gamel, and F. M. Talaat, published in Neural Computing and Applications in April 2024, explores the integration of Explainable Artificial Intelligence (XAI) into crop recommendation systems to enhance agricultural decision-making. In agricultural decision-making, selecting the right crops for a particular region, season, and soil type is a complex process that involves various factors such as weather conditions, soil health, and historical data. Traditional crop recommendation systems often rely on machine learning models to make predictions, but these models may lack transparency, making it difficult for farmers or agricultural experts to understand the reasoning behind the suggestions. This can hinder trust and adoption of these systems. The authors propose incorporating explainable AI techniques into crop recommendation systems, allowing farmers to better understand how and why certain crops are recommended for specific conditions. By providing clear, interpretable insights into the decision-making process, the system enhances the user's trust and confidence in the recommendations. This study likely involves applying techniques like decision trees, rule-based systems, or feature importance analysis to explain the predictions made by more complex machine learning models. The paper discusses the impact of this approach on improving agricultural practices, enabling more informed, data-driven decisions, and enhancing crop yield optimization while considering environmental sustainability. By adding transparency to AI-driven decision support systems, the research emphasizes the importance of combining advanced technology with human understanding, thereby improving the practical use of AI in agriculture.

Adaptive feature selection with deep learning MBi-LSTM model-based paddy plant leaf disease classification, R. K. Dubey and D. K. Choubey, 2023.

The paper titled "Adaptive Feature Selection with Deep Learning MBi-LSTM Model Based Paddy Plant Leaf Disease Classification" by R. K. Dubey and D. K. Choubey, published in Multimedia Tools

and Applications in August 2023, presents a novel approach for classifying paddy plant leaf diseases using an Adaptive Feature Selection technique combined with a Deep Learning MBi-LSTM (Multimodal Bidirectional Long Short-Term Memory) model. This study addresses the challenge of accurately identifying and classifying diseases in paddy plants, which is essential for effective crop management and yield optimization. The authors propose an adaptive feature selection method to improve the quality of input features used for classification, ensuring that the most relevant and informative features are chosen for training the model. This helps to reduce the complexity of the data and potentially increases the model's efficiency and accuracy. The key component of the proposed model is the MBi-LSTM, a type of Bidirectional LSTM (Long Short-Term Memory) network that is enhanced with multimodal inputs, which may include image data and other relevant agricultural features. LSTM networks are well-suited for sequential and time-dependent data, and the bidirectional aspect allows the model to capture information from both past and future data points. The use of a deep learning-based LSTM model for disease classification aims to capture temporal dependencies and complex patterns in the data, enabling the model to detect various paddy plant leaf diseases, such as bacterial blight or brown spot. Through this innovative approach, the paper highlights the potential of combining adaptive feature selection with deep learning techniques to improve the performance of disease classification systems, making them more robust and effective in real-world agricultural applications. The model can provide valuable support for farmers by offering timely disease detection, helping to mitigate crop damage, and promoting healthier, more resilient paddy crops.

Classification of glaucoma in retinal images using EfficientnetB4 deep learning model, A. Geetha and N. B. Prakash, 2022

The paper titled "Classification of Glaucoma in Retinal Images Using EfficientNetB4 Deep Learning Model" by A. Geetha and N. B. Prakash, published in Computers, Systems & Sciences Engineering in 2022, presents a deep learning-based approach for classifying glaucoma in retinal images using the EfficientNetB4 model. Glaucoma is a leading cause of blindness, and early detection through retinal image analysis is crucial for preventing vision loss. The authors employ EfficientNetB4, a state-of-the-art convolutional neural network architecture, to perform automated classification of retinal images for the detection of glaucoma. EfficientNetB4 is known for its efficient scaling mechanism, which balances the network's depth, width, and resolution to achieve high performance with fewer parameters. This characteristic makes it ideal for processing medical images, where accuracy and efficiency are critical. The paper focuses on the application of EfficientNetB4 for glaucoma detection, leveraging its ability to capture subtle patterns in retinal images that may indicate the presence of the disease. The model is trained on a dataset of retinal images, and its performance is compared with traditional image classification models to demonstrate its superior ability to detect glaucoma with high precision. This study highlights the potential of deep learning techniques, particularly EfficientNetB4, in the field of medical image analysis. By automating the detection of glaucoma, the system can assist healthcare professionals in diagnosing the disease early, improving patient outcomes, and reducing the burden on healthcare systems. The paper contributes to the growing body of research focused on applying deep learning models to medical image classification tasks, showcasing how advanced neural networks can be used to enhance diagnostic accuracy and support healthcare decision-making.

Semantic segmentation of microbial alterations based on SegFormer, W. M. Elmessery, D. V. Maklakov, T. M. El-Messery, D. A. Baranenko, J. Gutiérrez, M. Y. Shams, T. A. El-Hafeez, S. Elsayed, S. K. Alhag, F. S. Moghanm, M. A. Mulyukin, Y. Y. Petrova, and A. E. Elwakeel**,** 2024**.**

The paper titled "Semantic Segmentation of Microbial Alterations Based on SegFormer" by W. M. Elmessery, D. V. Maklakov, T. M. El-Messery, D. A. Baranenko, J. Gutiérrez, M. Y. Shams, T. A. El-Hafeez, S. Elsayed, S. K. Alhag, F. S. Moghanm, M. A. Mulyukin, Y. Y. Petrova, and A. E. Elwakeel, published in Frontiers in Plant Science in June 2024, introduces a deep learning-based method for semantic segmentation to analyze microbial alterations in plant images, using the SegFormer model. In agricultural and plant science research, understanding microbial alterations in plants is crucial for detecting diseases, pests, and other environmental stresses that can affect crop health. The authors employ SegFormer, a transformer-based deep learning model, for semantic segmentation tasks, which involves classifying each pixel in an image into a particular category, such as healthy tissue or microbial alterations. Semantic segmentation is particularly useful in identifying fine-grained details, like specific disease areas or microbial damage, within plant images. SegFormer, known for its high efficiency and performance in segmentation tasks, leverages transformers to capture global contextual information, enhancing its ability to detect and delineate complex patterns within plant images. By using this model, the authors aim to improve the accuracy and speed of detecting microbial damage, which is essential for early intervention and effective crop management. This study demonstrates the power of transformer-based models like SegFormer in plant disease and microbial detection, contributing to the broader field

of plant health monitoring. The research has significant implications for precision agriculture, where automated systems can assist in early disease detection, optimize crop management practices, and reduce the use of pesticides by providing timely, accurate information about plant health. The paper highlights the potential of deep learning technologies to transform agricultural practices by offering advanced tools for monitoring and improving crop yield and sustainability.

PROPOSED SYSTEM

The proposed model for paddy leaf disease classification represents a strategic advancement aimed at addressing the challenges associated with existing disease detection systems in agriculture. By utilizing the Xception architecture, the model capitalizes on the advantages of depth wise separable convolutions, which significantly reduce computational complexity while maintaining high accuracy. This makes the model more efficient, allowing for faster processing and making it suitable for deployment on resource-constrained devices, such as smartphones or low-cost embedded systems, which are commonly used by farmers in rural areas. In contrast to traditional convolutional neural networks (CNNs), the Xception model's use of separable convolutions allows it to focus on extracting more relevant features while reducing the number of parameters required for training. This makes the model less prone to overfitting and more capable of generalizing to new, unseen data. Moreover, the transfer learning approach, where the model is initialized with pre-trained weights from ImageNet, enables the network to leverage previously learned features, significantly reducing the amount of task-specific data needed for fine-tuning. This approach not only improves performance but also speeds up the training process, making it feasible to deploy the model even with limited labeled data.

The proposed model's architecture will be further enhanced with custom layers tailored to detect the unique visual patterns of paddy leaf diseases. These layers will help the model recognize subtle signs of disease in leaf images, such as slight discoloration or small lesions, which are crucial for early diagnosis and intervention. This is particularly important in paddy farming, where early detection of diseases can significantly reduce crop losses and the need for widespread pesticide use, promoting more sustainable agricultural practices. The model will also incorporate advanced optimization techniques, such as the Adam optimizer, which adapts the learning rate during training to accelerate convergence and improve model performance. The use of categorical cross-entropy loss ensures that the model is well-suited for multi-class classification tasks, accurately distinguishing between various types of paddy leaf diseases. One of the key aspects of the proposed model is its focus on accessibility and real-time use. The system will be designed with an intuitive, user-friendly interface that allows farmers to upload images of their crops directly from their smartphones or other mobile devices. Once uploaded, the model will quickly analyze the images and provide a disease diagnosis, enabling farmers to take prompt action to manage their crops effectively. This real-time feedback system will not only save time but also empower farmers to make informed decisions without needing to rely on expert intervention. Additionally, the model will be scalable and adaptable, capable of being integrated into existing agricultural platforms and IoT-based monitoring systems. This scalability will allow it to be deployed in various agricultural environments, from small-scale farms to larger commercial rice fields. The integration with IoT systems will enable continuous monitoring of crop health and provide a comprehensive solution for pest and disease management.

Overall, the proposed model aims to offer a highly accurate, efficient, and accessible solution for paddy leaf disease classification. By combining cutting-edge deep learning techniques with a focus on practical deployment and real-time usability, this system will help farmers improve crop management, reduce reliance on harmful pesticides, and contribute to the long-term sustainability of rice farming.

Proposed System Advantages:

- Efficient Architecture: Depthwise separable convolutions in Xception reduce computational complexity while maintaining high accuracy, enabling faster processing.
- Faster Training with Transfer Learning: Using pre-trained ImageNet weights, the model can quickly adapt to paddy leaf disease classification, requiring fewer labeled data.
- Real-Time Disease Detection: The model provides immediate disease diagnosis, allowing farmers to act quickly to manage crop health.
- Scalable and Accessible: The model can be deployed on low-cost devices like smartphones, making it accessible to farmers in rural, resource-limited areas.
- Sustainable Agricultural Practices: By enabling early disease detection, the system helps reduce pesticide use and promotes eco-friendly farming practices.

2. METHODOLOGY

The project, Paddy Leaf Disease Classification Using Xception: A High-Performance Deep Learning Approach, aims to address the critical challenges faced by paddy farmers in identifying and managing leaf diseases that affect crop yield and quality. Traditional methods of disease detection often rely on manual inspection, which can be time-consuming, error-prone, and dependent on expert knowledge. By automating this process through

advanced deep learning techniques, the project seeks to provide an efficient and accessible solution for farmers in both developed and developing regions. The Xception architecture is a key element of the proposed solution. Known for its high performance and reduced computational burden, Xception uses depthwise separable convolutions that break down traditional convolutions into simpler operations. This enables the model to efficiently learn complex patterns from the input images while keeping the computational costs low. As a result, the system can run on smartphones and other portable devices, making it possible for farmers to diagnose diseases in real time, directly in the field, without needing access to expensive infrastructure or cloud-based services. The system will be trained using a diverse dataset of labeled paddy leaf images, encompassing various diseases and healthy leaves. This dataset will serve as the foundation for the model to learn key features, such as discoloration, lesions, and spot patterns. The model's training will be enhanced using transfer learning, where the pre-trained weights from ImageNet are fine-tuned for the specific task of paddy leaf disease classification. This approach reduces the amount of training data needed and speeds up the model's ability to generalize, making it suitable for deployment even with limited datasets. A significant aspect of this project is its focus on real-time disease diagnosis. Once the model is trained, farmers will be able to upload images of their paddy leaves through a simple user interface on their mobile devices. The model will quickly analyze the image and return the predicted disease type, allowing farmers to take timely action and reduce the risk of crop damage. Early detection of diseases can prevent the spread of pathogens, reducing the need for harmful pesticides and promoting sustainable farming practices.

Additionally, the system will be designed to be scalable and adaptable to various environmental conditions. It will incorporate features such as disease-specific custom layers to enhance its ability to differentiate between subtle symptoms that may vary across different regions or growing conditions. This adaptability ensures that the system remains effective even as the model encounters new and previously unseen diseases or environmental factors. By providing a reliable, easy-to-use platform for disease classification, the project also seeks to empower farmers with the tools they need to manage their crops more efficiently. With access to accurate disease detection and early intervention, farmers can reduce costs associated with pesticide use, increase crop yield, and improve food security. Furthermore, the data collected from disease diagnoses can contribute to larger agricultural research initiatives, providing valuable insights into disease trends and the impact of climate change on crop health. In summary, the Paddy Leaf Disease Classification Using Xception project is poised to revolutionize how paddy farmers detect and manage diseases. By combining cutting-edge deep learning with user-friendly, real-time disease detection, this system has the potential to enhance agricultural productivity, reduce environmental impact, and improve the livelihoods of farmers worldwide.

MODULES

1) Data Collection:

The first step in the development of the Paddy Leaf Disease Classification Using Xception model is the collection of a high-quality dataset. The dataset should include images of both healthy paddy leaves and leaves infected with various diseases, such as bacterial blight, brown spot, and leaf smut. These images should represent a wide range of conditions, including different lighting, orientations, and environmental settings, to ensure the model can generalize well in real-world applications. Data can be sourced from publicly available agricultural image repositories, agricultural research centers, or through collaborations with farmers. Each image must be carefully labeled with the disease type or “healthy” status, as accurate labeling is critical for supervised learning.

2) Data Preprocessing: Resizing and Normalization:

After collecting the dataset, the next step is preprocessing the images for use in training the model. This involves resizing all images to a consistent size (such as 299x299 pixels), which is required for the Xception model. Resizing ensures that all input images have the same dimensions, making it easier for the model to process them. Once the images are resized, they undergo normalization, where pixel values are scaled to a range of [0, 1]. This helps the model train more efficiently by ensuring that all input data has similar scaling. This preprocessing step also improves the stability of the model and accelerates convergence during training.

3) Data Augmentation:

Data augmentation is a key strategy to improve the model's generalization ability. Given the potential for limited data, this step artificially increases the size and variety of the dataset by applying transformations to the existing images. Techniques such as rotating, flipping, zooming, shifting, and cropping images can simulate different environmental conditions and leaf orientations. These transformations help the model become more robust by teaching it to recognize disease patterns under various conditions. This ensures that the model does not overfit to the original dataset and can handle real-world variations in the appearance of paddy leaves.

4) Splitting the Dataset:

Once the data is preprocessed and augmented, it is divided into three main subsets: training, validation, and test sets. The training set is used to train the model, the validation set helps in tuning the model's hyperparameters and preventing overfitting, and the

test set is used to evaluate the final performance of the model. Typically, a split of 70-80% for training, 10-15% for validation, and the remaining portion for testing is used. This step ensures that the model is evaluated on unseen data, providing a true measure of its generalization ability.

5) Model Architecture Design:

At this stage, the architecture of the model is designed. The Xception model is used as the backbone, which has been proven to perform well on image classification tasks due to its efficient use of depthwise separable convolutions. This architecture is more computationally efficient than traditional convolutions while retaining high accuracy. The Xception model is initialized with pre-trained weights from ImageNet, a large and diverse image dataset. This approach, known as transfer learning, allows the model to leverage general features learned from ImageNet, such as edge and texture recognition, and apply them to the task of paddy leaf disease classification. The model is further customized with additional layers designed to focus on features specific to paddy leaf diseases.

6) Transfer Learning and Fine-Tuning:

Transfer learning is applied by using the pre-trained Xception model and then fine-tuning it on the paddy leaf disease dataset. The pre-trained weights from ImageNet are first loaded into the model. Fine-tuning involves unfreezing the top layers of the model and training them on the new dataset, allowing the model to adapt to specific features of paddy leaf diseases. The learning rate is adjusted to a smaller value during fine-tuning to prevent the model from losing the useful features it learned from ImageNet while adapting to the new task. Fine-tuning helps the model learn more detailed disease-related patterns without requiring a large amount of labeled data.

7) Model Optimization:

To improve the model's performance, optimization techniques are applied. The Adam optimizer is chosen because it adjusts the learning rate dynamically during training, helping the model converge faster. The loss function used is categorical cross-entropy, which is ideal for multi-class classification tasks like identifying various diseases. Regularization methods, such as dropout and batch normalization, are also implemented to prevent overfitting. Dropout works by randomly deactivating neurons during training, which forces the model to learn more robust features, while batch normalization helps in stabilizing the learning process by normalizing activations between layers.

8) Model Evaluation and Validation:

Once the model is trained, it is evaluated using the validation dataset to assess its performance and fine-tune hyperparameters. Cross-validation techniques, such as k-fold validation, can be applied to ensure the model generalizes well to different subsets of the data. Various metrics, including precision, recall, F1-score, and a confusion matrix, are calculated to assess the model's classification performance. These metrics provide insight into the model's ability to identify each disease class accurately and highlight any weaknesses or areas where the model may be misclassifying diseases.

9) Saving the Model:

After training and evaluation, the model is saved for future use. The trained model is serialized into a file format such as .h5 (for Keras models), which includes both the architecture and the learned weights. This allows the model to be loaded and reused later without the need for retraining. Saving the model makes it easy to deploy it into real-world applications, where it can be used to make predictions on new data without having to undergo the entire training process again.

10) User Interface Design for Making Predictions:

The saved model is integrated into a user-friendly interface to allow easy interaction by farmers or other users. The interface is designed to be simple, with an option to upload paddy leaf images directly from a smartphone or a web portal. Once the image is uploaded, it is preprocessed in the same way as the training data (resized, normalized) and passed through the trained model for prediction. The result is displayed to the user, showing the classification of the leaf as either healthy or affected by a specific disease. This real-time prediction helps farmers identify issues early and take appropriate action.

11) Prediction and Results Display:

After the user uploads an image and the model processes it, the predicted class (such as "Bacterial Blight" or "Brown Spot") is displayed, often along with a confidence score. This step provides real-time feedback to the user, enabling them to quickly diagnose the health of their crops. The user interface can also provide recommendations based on the predicted disease, offering actionable insights for pest management, treatment, and prevention. This is crucial for effective decision-making in the field, where timely intervention can significantly reduce crop damage and yield loss.

EXISTING TECHNIQUE: -

- **EfficientNet B4**

The existing technique for paddy leaf disease classification uses EfficientNet B4 with compound scaling and Swish activation, offering an efficient and accurate solution for disease detection in paddy crops. EfficientNet B4 is designed for high performance with fewer parameters, utilizing compound scaling to balance the model's depth, width, and resolution. This scaling method improves performance while minimizing computational costs, making the model suitable for complex image classification tasks like detecting diseases in paddy leaves.The model employs Swish activation, which provides smoother gradients compared to traditional activation functions like ReLU. This allows for faster

convergence and more effective learning, enabling the model to capture intricate patterns in the input data, such as subtle differences between healthy and diseased leaves. By incorporating Swish, the model performs better, especially in challenging tasks like disease detection.

In addition, the model benefits from transfer learning, where it is initialized with pre-trained weights from large datasets like ImageNet. This allows the model to leverage general features learned from a wide range of images, such as edges and textures. Fine-tuning these pre-trained weights on the specific paddy leaf disease dataset speeds up training and reduces the need for extensive labeled data.This combination of EfficientNet's efficient architecture, Swish activation, and transfer learning makes the model highly effective for paddy leaf disease classification. It can accurately detect diseases such as bacterial blight, brown spot, and sheath blight, helping farmers identify and manage diseases early. By providing timely disease diagnosis, the model helps reduce pesticide use and optimize crop health.Moreover, the model's efficient design ensures it can operate on devices with limited computational resources, such as smartphones. This makes it accessible for farmers in resource-constrained environments. The existing technique serves as a scalable and cost-effective solution for agricultural disease management, supporting sustainable farming practices and improving crop yields.

PROPOSED TECHNIQUE

- **Xception:**

The proposed algorithm for paddy leaf disease classification leverages the Xception model, a deep learning architecture based on depthwise separable convolutions, which has proven to be highly effective for image classification tasks. The model is initialized with pre-trained weights from ImageNet, allowing it to leverage general features learned from large-scale datasets before fine-tuning on the specific paddy leaf disease dataset. This transfer learning approach reduces the need for a large labeled dataset, speeds up training, and ensures better generalization on the specific task of disease detection. The Xception architecture is known for its high performance, using depthwise separable convolutions to reduce computational complexity while retaining a high capacity for learning intricate features from images. This makes it an ideal choice for paddy leaf disease classification, where the model needs to discern subtle differences between healthy and diseased leaves. The model's final layers are customized to fit the specific classification task, with a softmax activation function used to output the probabilities for each disease class.

The model is trained using the Adam optimizer, which adapts the learning rate throughout the training process, improving the model's ability to converge quickly and effectively. The loss function used is categorical cross-entropy, which is ideal for multi-class classification tasks like paddy leaf disease detection. This combination of Adam optimization and categorical cross-entropy ensures that the model minimizes the prediction error across multiple disease categories. To further improve the model's robustness, data augmentation techniques, such as rotation, flipping, and zooming, are employed to artificially increase the dataset's size and variation. This helps prevent overfitting by exposing the model to a broader range of possible image variations, improving its ability to generalize to new, unseen images.

The proposed model is also designed for real-time inference, allowing farmers and agricultural experts to classify leaf diseases quickly. The model can be deployed in a user-friendly interface, enabling farmers to upload images of paddy leaves and receive disease diagnoses in real time. By providing fast and accurate disease detection, the proposed system can assist farmers in making timely decisions regarding disease management and crop care. After training, the model is saved in an H5 format for easy deployment. The system's architecture allows for seamless integration with web or mobile applications, where users can upload leaf images, and the model will generate disease predictions. The system can also display the results alongside the image, providing users with both a visual and textual description of the disease, helping them take appropriate action to manage the disease and optimize crop yields. This combination of Xception architecture, transfer learning, and data augmentation ensures that the proposed model is not only highly accurate but also efficient and scalable for real-world agricultural applications. It offers a cost-effective solution to paddy leaf disease detection, making it accessible for farmers with limited computational resources, and contributes to sustainable farming practices by promoting early disease intervention and reducing pesticide usage.

SYSTEM ARCHITECTURE:



Fig: System Architecture

DATA FLOW DIAGRAM

Level 0



Level 1



Fig 4.9: Data Flow Diagrams

FUTURE ENHANCEMENT

Future enhancements to the proposed paddy leaf disease classification model could focus on several key areas to increase its performance, adaptability, and accessibility. First, expanding the dataset to include more diverse paddy leaf images from various regions and growing conditions would improve the model's ability to generalize and handle a wider range of diseases. Integrating multi-modal data, such as weather conditions, soil health, and other environmental factors, could further enhance the model's predictions by considering the broader context in which diseases spread, leading to more accurate and context-aware diagnoses. Additionally, the model could be integrated into a real-time mobile application, allowing farmers to easily upload images of their crops and receive immediate disease diagnoses. This would empower farmers in remote areas to take swift action against diseases. For deployment on resource-constrained devices, techniques like model compression could be applied to make the model smaller and faster without sacrificing accuracy. This would enable the model to run efficiently on smartphones or other low-power devices, facilitating wider adoption. Finally, improving the model's ability to detect rare diseases by enhancing its training with more specialized datasets or implementing techniques like semi-supervised learning could help the system identify diseases that are less commonly encountered, further increasing its value in diverse agricultural settings.

CONCLUSION

In conclusion, the proposed paddy leaf disease classification model using the Xception architecture offers a highly efficient and accurate solution for detecting and diagnosing diseases in paddy crops. By leveraging transfer learning, compound scaling, and Swish activation, the model is able to capture subtle differences between healthy and diseased leaves while maintaining computational efficiency. The system's ability to provide real-time disease predictions through a user-friendly interface can significantly aid farmers in making timely decisions regarding disease management, ultimately improving crop yields and promoting sustainable farming practices. While the model is already effective, future enhancements, such as incorporating multi-modal data, optimizing for mobile devices, and detecting rare diseases, hold the potential to further elevate its capabilities, making it an even more powerful tool for agricultural disease detection and management. By continuously refining and adapting the system, it can contribute to smarter, more efficient farming practices, reducing the overuse of pesticides and fostering healthier, more resilient crops.

REFERENCES

[1] M. Rahman, M. Islam, M. Rahaman, M. Sarkar, R. Ahmed, and M. Kabir, ''Identifying the threshold level of flooding for rice production in Bangladesh: An empirical analysis,'' J. Bangladesh Agricult. Univ., vol. 19, no. 20, pp. 243–250, 2021.

[2] G. S. Khush, ''What it will take to feed 5.0 billion rice consumers in 2030,'' Plant Mol. Biol., vol. 59, no. 1, pp. 1–6, Sep. 2005.

[3] S. Mohammad Fakhrul Islam and Z. Karim, ''World's demand for food and water: The consequences of climate change,'' in Desalination—Challenges and Opportunities. London, U.K.: IntechOpen, 2020, pp. 1–27.

[4] Agricultural Production—Our World in Data. Accessed: Jun. 25, 2024. [Online]. Available: https://ourworldindata.org/agricultural-production
[5] G. E. P. Box, G. M. Jenkins, G. C. Reinsel, and G. M. Ljung, Time Series Analysis: Forecasting and Control. Hoboken, NJ, USA: Wiley, 2015.
[6] M. Agarwal, S. K. Gupta, and K. K. Biswas, ''Development of efficient CNN model for tomato crop disease identification,'' Sustain. Comput. Informat. Syst., vol. 28, Dec. 2020, Art. no. 100407.
[7] R. Sharma, S. Das, M. K. Gourisaria, S. S. Rautaray, and M. Pandey, ''A model for prediction of paddy crop disease using CNN,'' in Proc. Prog. Comput., Anal. Netw. (ICCAN). Singapore: Springer, 2019, pp. 533–543.
[8] P. S. Thakur, T. Sheorey, and A. Ojha, ''VGG-ICNN: A lightweight CNN model for crop disease identification,'' Multimedia Tools Appl., vol. 82, no. 1, pp. 497–520, Jan. 2023.
[9] S. Iniyan, R. Jebakumar, P. Mangalraj, M. Mohit, and A. Nanda, ''Plant disease identification and detection using support vector machines and artificial neural networks,'' in Artificial Intelligence and Evolutionary Computations in Engineering Systems. Singapore: Springer, 2020, pp. 15–27.
[10] P. Patil, N. Yaligar, and S. M. Meena, ''Comparision of performance of classifiers-SVM, RF and ANN in potato blight disease detection using leaf images,'' in Proc. IEEE Int. Conf. Comput. Intell. Comput. Res. (ICCIC), Dec. 2017, pp. 1–5.
[11] Ü. Atila, M. Uçar, K. Akyol, and E. Uçar, ''Plant leaf disease classification using EfficientNet deep learning model,'' Ecol. Informat., vol. 61, Mar. 2021, Art. no. 101182.
[12] S. Sadiq, K. R. Malik, W. Ali, and M. M. Iqbal, ''Deep learning-based disease identification and classification in potato leaves,'' J. Comput. Biomed. Informat., vol. 5, no. 1, pp. 13–25, 2023.
[13] M. M. Anuar, A. A. Halin, T. Perumal, and B. Kalantar, ''Aerial imagery paddy seedlings inspection using deep learning,'' Remote Sens., vol. 14, no. 2, p. 274, Jan. 2022. [
14] M. Aggarwal, V. Khullar, N. Goyal, A. Singh, A. Tolba, E. B. Thompson, and S. Kumar, ''Pre-trained deep neural network-based features selection supported machine learning for rice leaf disease classification,'' Agriculture, vol. 13, no. 5, p. 936, Apr. 2023.
[15] F. Mashroor, I. F. Ishrak, S. M. Alvee, A. Jahan, M. N. I. Suvon, and S. Siddique, ''Rice paddy disease detection and disease affected area segmentation using convolutional neural networks,'' in Proc. IEEE Region 10 Conf. (TENCON), Dec. 2021, pp. 891–896.
[16] B. Paul, R. X. Rozario, A. Roy, S. Chakma, M. A. A. Wohra, K. R. Mahmud, and M. A. Rahman, ''Deep learning techniques for the automatic detection and classification of rice diseases,'' in Proc. Int. Conf. Inf. Commun. Technol. Competitive Strategies. Singapore: Springer, 2022, pp. 229–240.
[17] S. Saleki and J. Tahmoresnezhad, ''Agry: A comprehensive framework for plant diseases classification via pretrained EfficientNet and convolutional neural networks for precision agriculture,'' Multimedia Tools Appl., vol. 83, no. 24, pp. 64813–64851, Jan. 2024.
[18] F. Adnan, M. J. Awan, A. Mahmoud, H. Nobanee, A. Yasin, and A. M. Zain, ''EfficientNetB3-adaptive augmented deep learning (AADL) for multi-class plant disease classification,'' IEEE Access, vol. 11, pp. 85426–85440, 2023.
[19] M. W. Ahdi, Khalid, A. Kunaefi, B. A. Nugroho, and A. Yusuf, ''Convolutional neural network (CNN) EfficientNet-B0 model architecture for paddy diseases classification,'' in Proc. 14th Int. Conf. Inf. Commun. Technol. Syst. (ICTS), Oct. 2023, pp. 105–110.
[20] X. Bi and H. Wang, ''Double-branch deep convolutional neural networkbased rice leaf diseases recognition and classification,'' J. Agricult. Eng., vol. 55, no. 1, pp. 1–14, Oct. 2023.
[21] Paddy Doctor: Paddy Disease Classification | Kaggle. Accessed: Jun. 25, 2024. [Online]. Available: https://www.kaggle.com/competitions/paddydisease-classification
[22] M. Tan and Q. Le, ''EfficientNet: Rethinking model scaling for convolutional neural networks,'' in Proc. Int. Conf. Mach. Learn., 2019, pp. 6105–6114.
[23] M. Sandler, A. Howard, M. Zhu, A. Zhmoginov, and L.-C. Chen, ''MobileNetV2: Inverted residuals and linear bottlenecks,'' in Proc. IEEE/CVF Conf. Comput. Vis. Pattern Recognit., Jun. 2018, pp. 4510–4520.
[24] Q. Lin, Q. Leng, Z. Ding, C. Yan, and X. Xu, ''Optimizing contrail detection: A deep learning approach with EfficientNet-b4 encoding,'' 2024, arXiv:2404.14441.
[25] J. Fan, S. Upadhye, and A. Worster, ''Understanding receiver operating characteristic (ROC) curves,'' CJEM, vol. 8, no. 1, pp. 19–20, Jan. 2006.
[26] A. Geetha and N. B. Prakash, ''Classification of glaucoma in retinal images using EfficientnetB4 deep learning model,'' Comput. Syst. Sci. Eng., vol. 43, no. 3, pp. 1041–1055, 2022.
[27] R. K. Dubey and D. K. Choubey, ''An efficient adaptive feature selection with deep learning model-based paddy plant leaf disease classification,'' Multimedia Tools Appl., vol. 83, no. 8, pp. 22639–22661, Aug. 2023.
[28] B. Chang, Y. Wang, X. Zhao, G. Li, and P. Yuan, ''A general-purpose edgefeature guidance module to enhance vision transformers for plant disease identification,'' Expert Syst. Appl., vol. 237, Mar. 2024, Art. no. 121638.
[29] Rahman, M. W., Anjum, I., Mahi, S. A. H., Karim, M. F., Ahad, A., & Bijoy, M. H. I. (2025, February). Machine Learning-based Analyzing Impact of Remote Work Arrangements on Employee

Well-Being and Productivity. In 2025 International Conference on Electrical, Computer and Communication Engineering (ECCE) (pp. 1-6). IEEE.
[30] Kumar, Anuj. "Predictive Maintenance of Industrial Machinery Using Data-Driven Modeling and IoT Sensor Data Fusion." International Journal of Engineering Research and Application, Vol. 2, Issue 6, 2012, pp. 1712–1719
[31] Akinapalli, S. Agentic AI for Autonomous Data Engineering Operations in Cloud-Native Data Ecosystems.Journal of Information Systems Engineering and Management, 2024, 9(2)